

CONTAINER TYPES

TYPES	Tare Weight	Max* Cargo Cap.	Max Weight	Interior Cube	Door Opening		Measurements	Dimensions		
	(kg)	(Kg)	(Kg)	(m3)	Width	Height		Length	Width	Height
					(mm)	(mm)		(mm)	(mm)	(mm)
20' DRY FREIGHT:										
	2,080	21,920	24,000	33.2	2,346	2,282	Internal	5,910	2,340	2,388
							External	6,058	2,438	2,591
40' DRY FREIGHT:										
	3,550	26,930	30,480	67.6	2,337	2,280	Internal	12,044	2,342	2,380
							External	12,192	2,438	2,591
40' HC DRY:										
	4,150	26,330	30,480	76.2	2,338	2,585	Internal	12,032	2,350	2,695
							External	12,192	2,438	2,895
20' REFRIGERATED:										
	3,040	22,360	25,400	28.3	2,270	2,210	Internal	5,498	2,270	2,267
							External	6,058	2,438	2,591
40' REFRIGERATED:										
	4,480	21,520	26,000	58.4	2,290	2,265	Internal	11,570	2,285	2,250
							External	12,192	2,438	2,591
20' OPEN TOP:										
	2,050	21,950	24,000	32.2	2,336	2,233	Internal	5,792	2,340	2,286
							External	6,058	2,438	2,591
40' OPEN TOP:										
	3,800	27,020	30,820	65.6	2,337	2,280	Internal	12,043	2,338	2,272
							External	12,192	2,438	2,591
20' FLAT RACK:										
	2,845	22,555	25,400	28.9	Cargo access/ top: 5,908	Cargo access/ side: 5,508	Internal	5,702	2,387	2,327
							External	6,058	2,438	2,591
40' FLAT RACK:										
	5,180	39,820	45,000	67.0	Cargo access/ top: 12,020	Cargo access/ side: 11,730	Internal	11,820	2,148	2,095
							External	12,192	2,438	2,591